APPLICATIONS

CREALCO		88 88		<u></u>
casement windows	HOME	MANSION	MALL	TOWER
Wrap straight cut window	✓			
Casement 28 window	✓			
Casement 30.5 window	✓			
Casement 34 window		√	✓	
Casement 36 window		✓	✓	✓
Casement 38 window		√	✓	✓
SKYLINE Casement Window		✓	✓	✓
Casement 44 window			✓	
Edge thermal break casement window		✓	✓	✓
Serene casement widnow		✓	✓	✓

Looking for durability assurance? Ask for a Crealco FPD.

The FPD (Fenestration Performance Declaration) offers compliance and durability assurance on Crealco products supplied.

www.crealco-fpd.co.za





Crealco product range is available from the following Wispeco Appointed Stockists







































This brochure must be read in conjunction with the Installation, Cleaning & Maintenance Guidelines and Performance Certificates for the relevant system. The Manuals must also be used in conjunction with the design and cutting lists from the latest version of Starfront.

High Performance Window





The Crealco SKYLINE Casement Window (41mm Outer Frame) is a projected top and side hung window suitable for residential and commercial applications. The Crealco SKYLINE Casement Window offers various window configurations to best suite your fenestration requirements. The maximum permissible sizes for the SKYLINE Casement Window top hung opening pane is 2000 mm x 2000 mm (w x h) and for a side hung opening pane is 840 mm x 2000 mm (w x h).

FEATURES

- Designed to cater for high wind loads
- High performance window with excellent water drainage
- Deisgned for multi locking to accommodate large vents

GLAZING

- Designed to accommodate single glazing options between 4mm and 12 mm
- Designed to accommodate double glazing options between 16 mm and 26 mm

GASKET & SEALS

- Excellent quality colour-coded gaskets available, for ease of installation
- All gaskets & seals are locally available

FINISH

Available in a variety of popular architectural powder coating colours and finishes

HARDWARE

- Unique glass support blocks available for better drainage
- Standard casement handles or the Euro sash handle with multi-locking points (Heavy Duty Sash)
- Corner connectors that eliminate the need for crimping





This brochure must be read in conjunction with the Installation, Cleaning & Maintenance Guidelines and Performance Certificates for the relevant system. The Manuals must also be used in conjunction with the design and cutting lists from the latest version of Starfront.

This brochure must be read in conjunction with the Installation, Cleaning & Maintenance Guidelines and Performance Certificates for the relevant system. The Manuals must also be used in conjunction with the design and cutting lists from the latest version of Starfront.